

# Hybrid Monte Carlo in MICE

P. Franchini et al.

October 30, 2018

## Abstract

Proposal for the implementation of hybrid Monte Carlo to be used mainly for systematic studies in MICE data analysis.

## 1 Introduction

The MICE Monte Carlo is usually constituted of two parts. A G4BL simulation up to the second dipole D2 of particles generated at the target position and a full MAUS Monte Carlo up to the EMR detector. The simulation is fully automated to be executed on the GRID. A full Monte Carlo generation can be quite CPU consuming and unnecessary in case of systematic studies that might involve only changes at the cooling channel geometry level.

Specifications of the implementation of the hybrid MC on the GRID need to be agreed between users in order to

## 2 Proposal

Several hybrid versions of the official MICE Monte Carlo have been independently generated for different analysis by different users, generally without using the GRID infrastructure, running in Universities' clusters or on SCARF.

The general idea is:

- Generate a full MICE Monte Carlo dataset for a specific run (defined by the beam line settings, cooling channel currents, absorber material and geometry)
- Run the analysis in order to apply on the full simulation the desired set of preliminary cuts and produce a json file at the Tracker Station 5 position containing a defined list of variables
- Utilise a smearing procedure on the single beam file in order to generate as many different samples as necessary at the Tracker Station 5 position in order to produce enough statistics for the purpose of the study

- Run the MAUS simulation on each single sampled beam using the geometry defined by the user

The first two steps can be produced by the user, the beam copied over in the GRID job submission server together with the user-defined geometry or datacards, while the second two items have necessary to run on the GRID.

The variables that could be included in the beam file for each particle are:

- position and momentum at Tracker Station 5
- TOF0 position
- TOF1 position
- ???