

# A Proton-Based Muon Source for a Collider at CERN

*on behalf of the Muon Collider Collaboration*

## 1 Introduction

The muon collider collaboration was formed following the publication of the 2020 Update of the European Strategy for Particle Physics in June of this year [1]. Owing to the excellent potential for physics studies at a muon collider, the strategy update recommended that muon beam R&D should be considered a high-priority future initiative.

The collaboration is investigating two options for producing muons at CERN: either to fire protons onto a target to produce pions and other mesons, which decay into muons; or to fire high energy positrons onto a target near to the threshold for muon pair production. This Letter of Interest gives a brief overview of plans for the proton-based source.

The muon collider collaboration plans to adopt the proton source concept that was developed by the US Department of Energy funded Muon Accelerator Programme (MAP) [2]. The proton-based muon source is briefly described below.

## 2 MAP Muon Source

Pions, muons and other particles are produced by firing protons onto a liquid mercury target [3]. The target is contained in a 20 T magnet which serves both to confine the mercury jet and to confine the resultant secondary particles. The field is tapered to a 1.5 T constant solenoid field.

High momentum impurities are removed from the beam by means of a chicane created using a bent solenoid field, which introduces vertical dispersion [4]. High momentum particles get proportionately more dispersion and are removed on scrapers. A reverse bend returns the surviving particles with remarkably little emittance growth despite the large transverse emittance and huge momentum spread.

Low momentum protons are removed by a thick Beryllium window [4]; low momentum protons lose much more energy than muons and electrons in the material. The window marks the end of the active handling area.

Muons are first captured longitudinally [5]. The muon beam contains all momenta up to the limit of the chicane. Fast muons migrate to the front of the bunch while slow muons migrate to the end of the bunch. RF cavities are placed successively with gradually increasing voltage to adiabatically introduce microbunches into the beam. Frequency of successive cavities is selected to match the increasing time spread in the beam. RF cavities towards the end of the section are dephased such that the earlier, faster bunches experience a decelerating gradient and the later, slower bunches experience an accelerating gradient. This is repeated until the energy of the later bunches matches the energy of the earlier bunches.

An initial ionization cooling channel, capable of cooling both muon charges, reduces the 6D emittance of the muon beam [6]. In this scheme, the transverse field is alternated so that the beam passes through focusses. Dipole fields introduce dispersion, with oppositely charged muons having opposite dispersion. By carefully selecting position and size of wedge-shaped absorbers, the beam is cooled in all six dimensions.

The beam is separated into positive and negative muon species by means of another solenoid chicane [7]. Positive muons have the opposite dispersion to negative muons, enabling separation.

A series of combined dipoles and solenoids with wedges cools the beam in 6D. Because the charge is separated, more dispersion and tighter focussing can be introduced with consequently more cooling [8].

21 microbunches are merged longitudinally into 7 microbunches by means of a phase rotation scheme using slightly dephased RF cavities [9]. The bunch at the front of each set of 3 bunches undergoes a lower accelerating gradient and is slowed, while the bunch at the back experiences a higher accelerating gradient and is accelerated.

7 microbunches are merged transversely into 1 bunch by means of parallel transfer lines having different time delays. Each microbunch is kicked transversely into a different transfer line to get the appropriate time delay. The microbunches are brought together and stacked transversely into one bunch.

The beam then goes through another solenoid-dipole 6D cooling channel to further reduce its emittance [8].

A sequence of high field solenoids is used to introduce tight focussing around absorbers to further reduce the transverse emittance [10]. In order to reach very low emittances cooling is performed at low momentum, where transverse cooling is more effective at the expense of longitudinal heating.

The MAP scheme proposed acceleration to 5-10 GeV using a linac, followed by a linac with multiple dogbone arcs to recirculate the muon beam for reuse of the accelerating equipment for acceleration to higher energies (so-called ‘dogbone RLA’) [11]. This scheme was optimal for acceleration of a higher emittance neutrino factory beam and later upgrade to a muon collider. Following the RLAs, Rapid Cycling Synchrotrons were considered for acceleration to collision energy [12].

### 3 Plans

The muon collider collaboration will continue to investigate the issues surrounding the muon source.

Consideration will be given to any necessary modifications to the CERN complex to provide proton beam power and structure appropriate for the muon collider.

Technical risk in the target area may be avoided by adopting a solid target scheme. Such schemes have been considered previously, for example for the neutrino factory. The high instantaneous beam power makes solid targets challenging. Rotating targets [13], fluidised powder targets [14] and similar concepts may all be considered.

The final cooling is a priority, where further design work is required to meet the baseline cooling performance. Improvements to the cooling lattice will be considered, along with novel ideas such as parametric ionisation cooling [15] or [16] emittance exchange schemes. A final cooling ring has been proposed that would double the collider luminosity [17] and this will also be studied.

Additional constraints on the acceleration scheme due to neutrino radiation will be considered [18]. Novel technologies will be considered such as vertical FFAs [19]. The effects of muon decay radiation on the magnets will be considered.

A demonstrator for muon beam technologies having lower flux and energy than the muon collider will be considered.

### 4 Conclusions

The newly formed muon collider collaboration has begun studying options for a muon collider. Assessment of areas where improvements will significantly reduce technical risk or

yield better performance has begun. Optimisation of the existing design and new ideas will follow.

## Authors

J. Schieck,  
*Osterreichische Akademie der Wissenschaften, Vienna, Austria*

J. Tang,  
*Institute of High Energy Physics, Beijing, China*

M. Bonesini,  
*Sezione INFN Milano Bicocca, Milan, Italy*

D. Orestano, L. Tortora,  
*Universit Roma Tre and INFN, Rome, Italy*

Y. Mori,  
*Kyoto University, Kyoto, Japan*

T. du Pree,  
*Nikhef National Institute for Subatomic Physics, Amsterdam, Netherlands*

M. Chung,  
*UNIST, Ulsan, South Korea*

R. Ruber,  
*Uppsala University, Uppsala, Sweden*

N. Charitonidis, M. Krasny, R. Veness,  
*CERN, Geneva, Switzerland*

J. S. Berg,  
*Brookhaven National Laboratory, Long Island, USA*

B. Freemire, A. Liu,  
*Euclid Techlabs, LLC, Illinois, USA*

D. Bowring, S. Feher, P. Hanlet, C. Johnstone, Vl. Kashikhin, Va. Kashikhin, D. Neuffer,  
M. Popovic, A. Zlobin,  
*Fermi National Laboratory, Illinois, USA*

D. Kaplan, P. Snopok,  
*Illinois Institute of Technology, Illinois, USA*

Y. Onal,  
*University of Iowa, Iowa, USA*

Z. Liu,  
*University of Maryland, Maryland, USA*

C. Yoshikawa,  
*Formerly Muons Inc., Illinois, USA*

L. Cremaldi, D. Summers,  
*University of Oxford, Mississippi, USA*

K. T. McDonald,  
*Princeton University, New Jersey, USA*

S. A. Bogacz,  
*Thomas Jefferson National Accelerator Facility, Virginia, USA*

P. Kyberd,  
*Brunel University, London, UK*

M. Uchida,  
*University of Cambridge, Cambridge, UK*

J. C. Nugent, F. J. P. Soler,  
*University of Glasgow, Glasgow, UK*

R. Edgecock,  
*University of Huddersfield, West Yorkshire, UK*

P. Jurj, K. Long,  
*Imperial College, London, UK*

A. Bevan, L. Cremonesi, P. Hobson,  
*Queen Mary University of London, London, UK*

C. Densham, C. T. Rogers,  
*Rutherford Appleton Laboratory, Oxon, UK*

K. Ronald, C. Whyte,  
*University of Strathclyde, Glasgow, UK*

J. Back, G. Barker, S. Boyd,  
*University of Warwick, Warwickshire, UK*

## References

- [1] European Strategy Group, 2020 Update of the European Strategy Particle Physics. CERN-ESU-015 (2020).
- [2] Muon Accelerator Programme, <http://map.fnal.gov>.
- [3] H. G. Kirk and K. T. McDonald, The Target System Baseline, Muon Accelerator Programme Technical Note, MAP-doc-4412 (2011).
- [4] D. Stratakis et al., Design and optimization of a particle selection system for muon based accelerators, IPAC14 (2014).
- [5] D. Neuffer et al., Front end for a neutrino factory of muon collider, J. Inst. 12 (2017).
- [6] Y. Alexahin, Gas-filled HFOFO, Muon Accelerator Programme Technical Note, MAP-doc-4377 (2014).

- 
- [7] C. Yoshikawa, A charge separation study to enable the design of a complete muon cooling channel, NAPAC13 (2013).
  - [8] D. Stratakis and R. B. Palmer Phys. Rev. ST Accel. Beams 18, 031003 (2015).
  - [9] Y. Bao, Conceptual design and modeling of a six-dimensional bunch merging scheme for a muon collider, Phys. Rev. Accel. Beams 19 (2016).
  - [10] H. Sayed et al., High field – low energy muon ionization cooling channel, Phys. Rev. ST Accel. Beams 18 (2015).
  - [11] S.A. Bogacz, Muon Acceleration Concepts for NuMAX: "Dual-use" Linac and "Dog-bone" RLA, J. Inst. 13 (2018).
  - [12] J. S. Berg, Pulsed Synchrotrons for very rapid acceleration, MAP-doc-4395 (2014).
  - [13] J. Bennett et al., A high power radiation cooled target for a neutrino factory, EPAC00 (2000).
  - [14] C. Densham et al., The potential of fluidised power target technology in high power accelerator facilities, PAC09 (2009).
  - [15] J. Maloney, Numerical Studies of Optimization and Aberration Correction Methods for the Preliminary Demonstration of the Parametric Ionization Cooling (PIC) Principle in the Twin Helix Muon Cooling Channel, <https://arxiv.org/abs/1401.8256> (2014).
  - [16] D. Neuffer, New approaches to final cooling, MAP-doc-4403 (2014).
  - [17] T. L. Hart et al., Unconventional ideas for ionization cooling of muons, J. Inst. 15 (2020).
  - [18] B. King, Potential hazards from neutrino radiation at muon colliders, PAC99 (1999).
  - [19] S. Brooks, Vertical orbit excursion fixed field alternating gradient accelerators, Phys. Rev. ST AB 16, (2013).